

WHAT IS CLAIMED IS:

1. An image processing method for describing a real image as a virtual object using space data formed based on a photo image of the real object, and generating a  
5 virtual image of the virtual object using the space data, comprising the steps of:

capturing the photo image of the real object from a real camera viewpoint position while illuminating the real object by an illumination light source placed at a  
10 real illumination position;

converting the photo image into space data in the form of an object; and

storing the space data in a memory together with various illumination conditions at the real  
15 illumination position to allow a search at a later time.

2. The method according to claim 1, wherein the illumination position of the illumination light source is set at a plurality of different positions, and position information and an illumination condition at  
20 each illumination position are stored in the memory together with corresponding space data.

3. The method according to claim 1, wherein the camera viewpoint position is set at a plurality of different positions, and space data obtained at each  
25 viewpoint position is stored together with the viewpoint position information.

4. The method according to claim 1, wherein the space data is ray space theory data.

5. The method according to claim 1, wherein the illumination condition is varied in a plurality of ways per illumination position, and space data corresponding to the individual illumination conditions are stored in the memory.

6. An image processing method for describing a real image as a virtual object using space data formed based on a photo image of the real object, and generating a virtual image of the virtual object using the space data, comprising the steps of:

storing space data generated from a photo image together with a real camera viewpoint position, and an illumination position and illumination condition of a real illumination light source;

generating coordinates of a virtual image of an object at a user viewpoint position on the basis of the real camera viewpoint position and the space data; and

correcting pixel values of the virtual image on the basis of the real illumination position and real illumination condition of the real illumination light source, and a virtual illumination position and virtual illumination condition set for a virtual illumination light source.

7. The method according to claim 6, wherein the illumination position of the real illumination light source is set at a plurality of different positions, and position information and an illumination condition  
5 at each illumination position are stored in the memory together with corresponding space data.
8. The method according to claim 6, wherein the real camera viewpoint position is set at a plurality of different positions, and space data obtained at each  
10 viewpoint position is stored together with the viewpoint position information.
9. The method according to claim 6, wherein the space data is ray space theory data.
10. The method according to claim 6, further  
15 comprising the step of changing and setting an illumination condition of the virtual illumination light source to be an arbitrary value, and wherein the correction step includes the step of correcting the pixel values in accordance with the changed  
20 illumination condition.
11. The method according to claim 6, wherein when a plurality of virtual light sources are ON at the same time, a plurality of correction results which are corrected in accordance with the respective virtual  
25 illumination light sources are added for one pixel position to obtain a final pixel value.

12. The method according to claim 6, wherein when some of a plurality of virtual light sources are ON at the same time, a plurality of correction results which are corrected in accordance with the respective ON
- 5 virtual illumination light sources are added for one pixel position to obtain a final pixel value.
13. The method according to claim 6, further comprising the steps of:
- determining if the corrected pixel value
- 10 saturates; and
- virtually changing illumination conditions of some or all of the virtual light sources in a direction to decrease luminance or illuminance of an illumination when the pixel value saturates, and
- 15 wherein the correction step is executed again in accordance with the changed illumination condition.
14. The method according to claim 6, wherein the illumination condition includes information indicating whether or not an illumination is turned on.
- 20 15. The method according to claim 6, wherein the illumination condition includes illuminance or luminance.
16. The method according to claim 6, wherein the illumination condition includes a relative position
- 25 between the virtual light source and object.

17. The method according to claim 6, wherein the illumination condition includes color of illumination.

18. An image processing apparatus for describing a real image as a virtual object using space data formed  
5 based on a photo image of the real object, and generating a virtual image of the virtual object using the space data, comprising:

means for capturing the photo image of the real object from a real camera viewpoint position while  
10 illuminating the real object by an illumination light source placed at a real illumination position;

conversion means for converting the photo image into space data in the form of an object for each pixel; and

15 means for storing the space data in a memory together with various illumination conditions at the real illumination position to allow a search at a later time.

19. The apparatus according to claim 18, wherein the  
20 illumination position of the illumination light source is set at a plurality of different positions, and position information and an illumination condition at each illumination position are stored in the memory together with corresponding space data.

25 20. The apparatus according to claim 18, wherein the camera viewpoint position is set at a plurality of

different positions, and space data obtained at each viewpoint position is stored together with the viewpoint position information.

21. The apparatus according to claim 18, wherein the  
5 space data is ray space theory data.

22. The apparatus according to claim 18, wherein the illumination condition is varied in a plurality of ways per illumination position, and space data corresponding to the individual illumination conditions are stored in  
10 the memory.

23. An image processing apparatus for describing a real image as a virtual object using space data formed based on a photo image of the real object, and generating a virtual image of the virtual object using  
15 the space data, comprising:

means for storing space data in the form of an object for each pixel of a photo image together with a real camera viewpoint position, and an illumination position and illumination condition of a real  
20 illumination light source;

generation means for generating coordinates of a virtual image of an object at a user viewpoint position on the basis of the real camera viewpoint position and the space data; and

25 correction means for correcting pixel values of the virtual image on the basis of the real illumination

position and real illumination condition of the real illumination light source, and a virtual illumination position and virtual illumination condition set for a virtual illumination light source.

5 24. The apparatus according to claim 23, wherein the illumination position of the real illumination light source is set at a plurality of different positions, and position information and an illumination condition at each illumination position are stored in the memory  
10 together with corresponding space data.

25. The apparatus according to claim 23, wherein the real camera viewpoint position is set at a plurality of different positions, and space data obtained at each viewpoint position is stored together with the  
15 viewpoint position information.

26. The apparatus according to claim 23, wherein the space data is ray space theory data.

27. The apparatus according to claim 23, further comprising means for changing and setting an  
20 illumination condition of the virtual illumination light source to be arbitrary values, and wherein said correction means corrects the pixel values in accordance with the changed illumination condition.

28. The apparatus according to claim 23, wherein when  
25 a plurality of virtual light sources are ON at the same time, a plurality of correction results which are

corrected in accordance with the respective virtual illumination light sources are added for one pixel position to obtain a final pixel value.

29. The apparatus according to claim 23, wherein when  
5 some of a plurality of virtual light sources are ON at the same time, a plurality of correction results which are corrected in accordance with the respective ON virtual illumination light sources are added for one pixel position to obtain a final pixel value.

10 30. The apparatus according to claim 23, further comprising:

means for determining if the corrected pixel value saturates; and

means for virtually changing illumination  
15 conditions of some or all of the virtual light sources in a direction to decrease luminance or illuminance of an illumination when the pixel value saturates, and

wherein said correction means is executed again in accordance with the changed illumination condition.

20 31. The apparatus according to claim 23, wherein the illumination condition includes information indicating whether or not an illumination is turned on.

32. The apparatus according to claim 23, wherein the illumination condition includes illuminance or  
25 luminance.



33. The apparatus according to claim 23, wherein the illumination condition includes a relative position between the virtual light source and object.

34. The apparatus according to claim 23, wherein the  
5 illumination condition includes color of illumination.

35. An image processing method for generating a shadow image of a virtual object itself in a virtual space, comprising the steps of:

sensing an image of a real object by a camera  
10 while illuminating the real object corresponding to the virtual object from a light source at a predetermined illumination position;

extracting a silhouette of the real object from the image of the real object;

15 adding preferred image information as a shadow to pixels in the silhouette; and

storing the silhouette image together with position information of the light source, the silhouette image being able to be found by search and  
20 retrieved at a later time.

36. The method according to claim 35, wherein the preferred image information includes a predetermined black pixel value and a predetermined transparency value.

25 37. The method according to claim 35, wherein the silhouette image undergoes a blur process.

38. The method according to claim 37, wherein the degree of blur is changed in correspondence with distance from the virtual object to a virtual light source.

5 39. The method according to claim 35, wherein a viewpoint position of the camera matches the position of the illumination light source.

40. An image processing method for generating a shadow image of a virtual object itself in a virtual  
10 space, comprising the steps of:

storing space data of the virtual object, a shadow image of a real object corresponding to the virtual object, and a position of an illumination light source upon forming the shadow image in a predetermined  
15 memory;

reading out the shadow image from the memory in accordance with a position of a virtual illumination, and a relative position of the virtual object; and

mapping the readout shadow image on a  
20 predetermined mapping plane.

41. The method according to claim 40, wherein the mapping plane is determined on the basis of a bounding box of the virtual object.

42. The method according to claim 40, further  
25 comprising the step of changing and setting an illumination condition of the virtual illumination

light source to be an arbitrary value, and wherein the correction step includes the step of correcting the pixel values in accordance with the changed illumination condition.

5 43. The method according to claim 40, wherein when a plurality of virtual light sources are ON at the same time, a plurality of correction results which are corrected in accordance with the respective virtual illumination light sources are added for one pixel  
10 position to obtain a final pixel value.

44. The method according to claim 40, wherein when some of a plurality of virtual light sources are ON at the same time, a plurality of correction results which are corrected in accordance with the respective ON  
15 virtual illumination light sources are added for one pixel position to obtain a final pixel value.

45. The method according to claim 40, wherein when the illumination is located at a high-level position, a mapping plane with a simple shape is generated.

20 46. An image processing apparatus for generating a shadow image of a virtual object itself in a virtual space, comprising:

means for sensing an image of a real object by a camera while illuminating the real object corresponding  
25 to the virtual object from a light source at a predetermined illumination position;

means for extracting a silhouette of the real object from the image of the real object;

means for adding preferred image information as a shadow to pixels in the silhouette; and

5 means for storing the edge image together with position information of the light source, the silhouette image being able to be found by search and retrieved at a later time.

47. The apparatus according to claim 46, wherein the  
10 preferred image information includes a predetermined black pixel value and a predetermined transparency value.

48. The apparatus according to claim 46, wherein when  
15 the viewpoint position of the camera is different from the position of the light source, the silhouette image is corrected by re-projecting the silhouette image to have the position of the light source as a viewpoint position.

49. The apparatus according to claim 46, further  
20 comprising means for performing a blur process of the silhouette image.

50. The apparatus according to claim 49, wherein the  
25 degree of blur is changed in correspondence with distance from the virtual object to a virtual light source.

51. The apparatus according to claim 46, wherein a viewpoint position of the camera matches the position of the illumination light source.

52. An image processing apparatus for generating a  
5 shadow image of a virtual object itself in a virtual space, comprising the steps of:

means for storing space data of the virtual object, a shadow image of a real object corresponding to the virtual object, and a position of an  
10 illumination light source upon forming the shadow image in a predetermined memory;

means for reading out the shadow image from the memory in accordance with a position of a virtual illumination, and a relative position of the virtual  
15 object; and

means for mapping the readout shadow image on a predetermined mapping plane.

53. The apparatus according to claim 52, wherein the mapping plane is determined on the basis of a bounding  
20 box of the virtual object.

54. The apparatus according to claim 52, further comprising means for changing and setting an illumination condition of the virtual illumination light source to be an arbitrary value, and wherein said  
25 correction means corrects the pixel values in accordance with the changed illumination condition.

55. The apparatus according to claim 52, wherein when a plurality of virtual light sources are ON at the same time, a plurality of correction results which are corrected in accordance with the respective virtual  
5 illumination light sources are added for one pixel position to obtain a final pixel value.

56. The apparatus according to claim 52, wherein when some of a plurality of virtual light sources are ON at the same time, a plurality of correction results which  
10 are corrected in accordance with the respective ON virtual illumination light sources are added for one pixel position to obtain a final pixel value.

57. The apparatus according to claim 52, wherein when the illumination is located at a high-level position, a  
15 mapping plane with a simple shape is generated.

58. An image processing method for generating a shadow image of a virtual object itself in a virtual space, comprising the steps of:

extracting a silhouette of the virtual object  
20 viewed from a predetermined illumination position on the basis of space data which expresses the virtual object;

adding preferred image information as a shadow to pixels in the silhouette; and

25 mapping the silhouette image on a predetermined mapping plane.

59. An image processing apparatus for generating a shadow image of a virtual object itself in a virtual space, comprising:

means for extracting a silhouette of the virtual  
5 object viewed from a predetermined illumination  
position on the basis of space data which expresses the  
virtual object;

means for adding preferred image information as a  
shadow to pixels in the silhouette; and

10 means for mapping the silhouette image on a  
predetermined mapping plane.

60. An image processing apparatus for mixing a  
virtual space with a real space illuminated by a real  
illumination device, and presenting the mixed space,  
15 comprising:

change means for changing an illumination  
condition of the illumination device;

first setting means for setting an illumination  
program parameter value corresponding to a value of the  
20 changed illumination condition;

rendering means for rendering a virtual image  
using a predetermined illumination condition program  
parameter, and mixing the virtual image with the real  
space; and

25 second setting means for setting, in a rendering  
routine of the virtual image of said rendering means,

the illumination condition program parameter set by  
said setting means in correspondence with the  
illumination condition changed by said change means.

61. The apparatus according to claim 60, wherein the  
5 illumination condition includes one of illuminance,  
color, and an illumination direction.

62. The apparatus according to claim 60, wherein said  
change means comprises GUI means operated by a user to  
display control buttons for graphically changing  
10 illuminance, color, and an illumination direction of  
the illumination device on a display screen.

63. The apparatus according to claim 60, wherein said  
change means comprises GUI means operated by a user,  
and said GUI means displays an image that simplifies  
15 the illumination device and allows the user to instruct  
to change a given illumination condition by designating  
a portion to be adjusted in the image using a pointing  
device.

64. The apparatus according to claim 60, wherein said  
20 first setting means includes means for reading out a  
parameter pre-stored in a predetermined memory.

65. An image processing method for mixing a virtual  
space with a real space illuminated by a real  
illumination device, comprising:

25 the step of changing an illumination condition of  
the illumination device;



the first setting step of setting an illumination program parameter value corresponding to a value of the changed illumination condition;

the step of rendering a virtual image using a  
5 predetermined illumination condition program parameter, and mixing the virtual image with the real space; and

the second setting step of setting, in a rendering routine of the virtual image, the illumination condition program parameter set in  
10 correspondence with the illumination condition changed in the change step.

66. The method according to claim 65, wherein the first setting step includes the step of reading out a parameter pre-stored in a predetermined memory.

15 67. The method according to claim 65, wherein the change step includes the step of displaying a GUI operated by a user to display control buttons for graphically changing illuminance, color, and an illumination direction of the illumination device on a  
20 display screen.

68. The method according to claim 65, wherein the change step includes the step of displaying a GUI operated by a user, and the GUI displays an image that simplifies the illumination device and allows the user  
25 to instruct to change a given illumination condition by

designating a portion to be adjusted in the image using a pointing device.

69. A storage medium that stores a control program for making a computer execute an image process for  
5 describing a real image as a virtual object using space data formed based on a photo image of the real object, and generating a virtual image of the virtual object using the space data, said control program including:

10 a code of the capture step of capturing the photo image of the real object from a real camera viewpoint position while illuminating the real object by an illumination light source placed at a real illumination position;

15 a code of the conversion step of converting the photo image into space data in the form of an object; and

20 a code of the storage step of storing the space data in a memory to allow a search together with various illumination conditions at the real illumination position.

70. A storage medium that stores a control program for making a computer execute an image process for describing a real image as a virtual object using space data formed based on a photo image of the real object,  
25 and generating a virtual image of the virtual object using the space data, said control program including:

a code of the storage step of storing space data generated from a photo image together with a real camera viewpoint position, and an illumination position and illumination condition of a real illumination light source;

a code of the generation step of generating coordinates of a virtual image of an object at a user viewpoint position on the basis of the real camera viewpoint position and the space data; and

a code of the correction step of correcting pixel values of the virtual image on the basis of the real illumination position and real illumination condition of the real illumination light source, and a virtual illumination position and virtual illumination condition set for a virtual illumination light source.

71. A storage medium that stores a control program for making a computer execute an image process for generating a shadow image of a virtual object itself in a virtual space, said control program including:

a code of the image sensing step of sensing an image of a real object by a camera while illuminating the real object corresponding to the virtual object from a light source at a predetermined illumination position;

a code of the extraction step of extracting a silhouette of the real object from the image of the real object;

a code of the addition step of adding preferred  
5 image information as a shadow to pixels in the silhouette; and

a code of the storage step of storing the silhouette image together with position information of the light source, the silhouette image being able to be  
10 found by search and retrieved at a later time.

72. A storage medium that stores a control program for making a computer execute an image process for generating a shadow image of a virtual object itself in a virtual space, said control program including:

15 a code of the storage step of storing space data of the virtual object, a shadow image of a real object corresponding to the virtual object, and a position of an illumination light source upon forming the shadow image in a predetermined memory;

20 a code of the read-out step of reading out the shadow image from the memory in accordance with a position of a virtual illumination, and a relative position of the virtual object; and

a code of the mapping step of mapping the readout  
25 shadow image on a predetermined mapping plane.

73. A storage medium that stores a control program for making a computer execute an image process for generating a shadow image of a virtual object itself in a virtual space, said control program including:

5 a code of the extraction step of extracting a silhouette of the virtual object viewed from a predetermined illumination position on the basis of space data which expresses the virtual object;

10 a code of the addition step of adding preferred image information as a shadow to pixels in the silhouette; and

a code of the mapping step of mapping the silhouette image on a predetermined mapping plane.

74. A storage medium that stores a control program for making a computer execute an image process for generating a shadow image of a virtual object itself in a virtual space, said control program including:

a code of the step of changing an illumination condition of the illumination device;

20 a code of the first setting step of setting an illumination program parameter value corresponding to a value of the changed illumination condition;

a code of the step of rendering a virtual image using a predetermined illumination condition program parameter, and mixing the virtual image with the real space; and

25

a code of the second setting step of setting, in  
a rendering routine of the virtual image, the  
illumination condition program parameter set in  
correspondence with the illumination condition changed  
5 in the change step.